



- NOTES:
- 1.DISPLAY : TFT
  - 2.DRIVE IC: Source HX8282-A02 Gate HX8696-A
  - 3.POLARIZER MODE: TRANSMISSIVE/POSITIVE
  - 4.BACKLIGHT: 48X2 PCS LEDS
  - 5.OPERATING TEMP: -20°C ~ 70°C
  - 6.STORAGE TEMP: -30°C ~ 80°C
  - 7.General Tolerance : ±0.2mm
  - 8.RoHS Compliant

LCM-PIN NAME	LCM-PIN NAME	LCM-PIN NAME	LCM-PIN NAME	LCM-PIN NAME	TP-PIN NAME
1 VCC	9 RX1W+	17 RX6L1H-	25 NC	1 GND	
2 VCC	10 VSS	18 RX6L1H+	26 NC	2 SDA	
3 V-E/D1	11 RX1W-	19 GND	27 NC	3 SOL	
4 SOL	12 RX1W+	20 RX1W+	28 NC	4 INT	
5 SDA	13 VSS	21 RX1W+	29 NC	5 REST	
6 VSS	14 RX1W-	22 VSS	30 DTH	6 VCC	
7 VSS	15 RX1W+	23 NC			
8 RX1W-	16 VSS	24 NC			

DRAWN BY:	TITLE:	SCALE:	UNIT: mm
CHECKED BY:	DWG NO:		
APPROVED BY:	DWG NAME:	SHEET NO:	OF
CONFIRMED BY:			